


FEATURES

- Ideally suited for automatic insertion
- Epitaxial planar die construction
- Complementary NPN type available(BC817)



MECHANICAL DATA

- SOT-23 small outline plastic package
- Epoxy UL: 94V-0
- Mounting position: Any



APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter		Symbol	Value	Unit
Collector-Base Voltage	BC807	V_{CBO}	-50	V
	BC808		-30	
Collector-Emitter Voltage	BC807	V_{CEO}	-45	V
	BC808		-25	
Emitter-Base Voltage		V_{EBO}	-5	V
Collector Current		I_C	-0.5	A
Collector Power Dissipation		P_C	0.3	W
Junction Temperature		T_J	150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55~+150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS (T_A=25°C)


Parameter		Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector-base breakdown voltage	BC807	V _{CBO}	I _C =-10μA, I _E =0	-50			V
	BC808			-30			
Collector-emitter breakdown voltage	BC807	V _{CEO}	I _C =-10mA, I _B =0	-45			V
	BC808			-25			
Emitter-base breakdown voltage		V _{EBO}	I _E =-1μA, I _C =0	-5			V
Collector cut-off current		I _{CBO}	V _{CB} =-45V, I _E =0			-0.1	μA
Collector cut-off current		I _{CEO}	V _{CE} =-40V, I _B =0			-0.2	μA
Emitter cut-off current		I _{EBO}	V _{EB} =-4V, I _C =0			-0.1	μA
DC current gain	BC807-16,BC808-16	h _{FE(1)}	V _{CE} =-1V, I _C =-100mA	100		250	
	BC807-25,BC808-25			160		400	
	BC807-40,BC808-40			250		600	
Collector-emitter saturation voltage		V _{CE(sat)}	I _C =-500mA, I _B =-50mA			-0.7	V
Base-emitter saturation voltage		V _{BE(sat)}	I _C =-500mA, I _B =-50mA			-1.2	V
Transition frequency		f _T	V _{CE} =-5V, I _C =-10mA, f=100MHz	100			MHz

MARKING


Part Number	BC807-16	BC807-25	BC807-40	BC808-16	BC808-25	BC808-40
Marking	5A	5B	5C	9GA	9GB	9GC

TYPICAL CHARACTERISTICS


Static Characteristic




h_{FE} — I_C







$V_{CE\text{ sat}}$ — I_C




$V_{BE\text{ sat}}$ — I_C






SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C




SOT-23 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.80	3.05	0.110	0.120
B	1.20	1.40	0.047	0.055
C	0.90	1.15	0.035	0.045
D	0.37	0.50	0.015	0.020
G	1.75	2.05	0.069	0.081
H	0.01	0.100	0.001	0.004
J	0.085	0.180	0.003	0.007
K	0.35	0.69	0.014	0.029
L	0.89	1.02	0.035	0.040
S	2.10	2.65	0.083	0.104
V	0.45	0.60	0.018	0.024

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.71	0.97	0.028	0.038
B	1.88	2.13	0.074	0.084
C	0.71	0.97	0.028	0.038
D	0.81	1.07	0.032	0.042

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
BC807-BC808	SOT-23	3000PCS	7"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.