


FEATURES

- | Planar Die Construction

- | 150mW Power Dissipation

- | Zener Voltages From 2.4 – 43V

- | Meet AEC-Q101 Requirements



SOD-523



Schematic Symbol

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS (T_A=25°C)

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	150	mW
Maximum forward voltage at I _F =10mA	V _F	0.9	V
Thermal Resistance from Junction to Ambient	R _{θJA}	833	°C/W
Storage temperature range	T _J , T _{STG}	-55 to +150	°C





ELECTRICAL CHARACTERISTICS

Part Number	Device Marking Code	Zener Voltage Range (Note 1)				Maximum Zener Impedance (Note 2)			Maximum Reverse Current		Typical temperature coefficient @I _{ZT} mV/°C	
		V _Z @I _{ZT}			I _{ZT}	Z _{ZT} @I _{ZT}	Z _{ZK} @I _{ZK}		I _R	V _R	Min	Max
		Nom(V)	Min(V)	Max(V)	(mA)	(Ω)	(mA)	(μA)	(V)			
BZX584C2V4Q	Z11Q	2.4	2.20	2.60	5	100	600	1.0	50	1.0	-3.5	0
BZX584C2V7Q	Z12Q	2.7	2.5	2.9	5	100	600	1.0	20	1.0	-3.5	0
BZX584C3V0Q	Z13Q	3.0	2.8	3.2	5	95	600	1.0	10	1.0	-3.5	0
BZX584C3V3Q	Z14Q	3.3	3.1	3.5	5	95	600	1.0	5	1.0	-3.5	0
BZX584C3V6Q	Z15Q	3.6	3.4	3.8	5	90	600	1.0	5	1.0	-3.5	0
BZX584C3V9Q	Z16Q	3.9	3.7	4.1	5	90	600	1.0	3	1.0	-3.5	0
BZX584C4V3Q	Z17Q	4.3	4.0	4.6	5	90	600	1.0	3	1.0	-3.5	0
BZX584C4V7Q	Z1Q	4.7	4.4	5.0	5	80	500	1.0	3	2.0	-3.5	0.2
BZX584C5V1Q	Z2Q	5.1	4.8	5.4	5	60	480	1.0	2	2.0	-2.7	1.2
BZX584C5V6Q	Z3Q	5.6	5.2	6.0	5	40	400	1.0	1	2.0	-2.0	2.5
BZX584C6V2Q	Z4Q	6.2	5.8	6.6	5	10	150	1.0	3	4.0	0.4	3.7
BZX584C6V8Q	Z5Q	6.8	6.4	7.2	5	15	80	1.0	2	4.0	1.2	4.5
BZX584C7V5Q	Z6Q	7.5	7.0	7.9	5	15	80	1.0	1	5.0	2.5	5.3
BZX584C8V2Q	Z7Q	8.2	7.7	8.7	5	15	80	1.0	0.7	5.0	3.2	6.2
BZX584C9V1Q	Z8Q	9.1	8.5	9.6	5	15	100	1.0	0.5	6.0	3.8	7.0
BZX584C10Q	Z9Q	10	9.4	10.6	5	20	150	1.0	0.2	7.0	4.5	8.0
BZX584C11Q	Y1Q	11	10.4	11.6	5	20	150	1.0	0.1	8.0	5.4	9.0
BZX584C12Q	Y2Q	12	11.4	12.7	5	25	150	1.0	0.1	8.0	6.0	10.0
BZX584C13Q	Y3Q	13	12.4	14.1	5	30	170	1.0	0.1	8.0	7.0	11.0
BZX584C15Q	Y4Q	15	13.8	15.6	5	30	200	1.0	0.1	10.5	9.2	13.0
BZX584C16Q	Y5Q	16	15.3	17.1	5	40	200	1.0	0.1	11.2	10.4	14.0
BZX584C18Q	Y6Q	18	16.8	19.1	5	45	225	1.0	0.1	12.6	12.4	16.0
BZX584C20Q	Y7Q	20	18.8	21.2	5	55	225	1.0	0.1	14.0	14.4	18.0
BZX584C22Q	Y8Q	22	20.8	23.3	5	55	250	1.0	0.1	15.4	16.4	20.0
BZX584C24Q	Y9Q	24	22.8	25.6	5	70	250	1.0	0.1	16.8	18.4	22.0
BZX584C27Q	Y10Q	27	25.1	28.9	2	80	300	0.5	0.1	18.9	21.4	25.3
BZX584C30Q	Y11Q	30	28.0	32.0	2	80	300	0.5	0.1	21.0	24.4	29.4
BZX584C33Q	Y12Q	33	31.0	35.0	2	80	325	0.5	0.1	23.1	27.4	33.4
BZX584C36Q	Y13Q	36	34.0	38.0	2	90	350	0.5	0.1	25.2	30.4	37.4
BZX584C39Q	Y14Q	39	37.0	41.0	2	130	350	0.5	0.1	27.3	33.4	41.2
BZX584C43Q	Y15Q	43	40.0	46.0	2	100	700	1.0	0.1	32.0	10.0	12.0


Notes:

1. Tested with pulses, period=5ms, pulse width =300μs.
2. f = 1 kHz


CHARACTERISTIC CURVES

Zener Characteristics (V_z Up to 10 V)

Zener Characteristics (11 V to 43 V)

Temperature Coefficients

Typical Leakage Current



Typical Capacitance



Effect of Zener Voltage on Zener Impedance




Power Derating Curve




SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak)		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C




SOD-523 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.50	0.80	0.020	0.031
b	0.25	0.35	0.010	0.014
c	0.07	0.20	0.003	0.008
D	0.70	0.90	0.028	0.035
E	1.10	1.30	0.043	0.051
E1	1.50	1.70	0.059	0.067
L	0.15	0.25	0.006	0.010

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters	Inches
	Min.	Min.
A	2.00	0.0787
B	0.60	0.0236
C	0.70	0.0276

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
BZX584CxxxQ	SOD-523	3000PCS	7"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware' s global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.