


FEATURES


- | Low Collector-Emitter saturation voltage $V_{CE(sat)}$
- | High collector current capability



SOT-223

MECHANICAL DATA


- | Case: SOT-223
- | Molding compound: UL flammability classification rating 94V-0
- | Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



Marking

APPROVALS

- RoHS** | Compliance with 2011/65/EU
- HF** | Compliance with IEC61249-2-21:2003



Schematic Symbol

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)


Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V_{CBO}	-180	V
Collector-Emitter Breakdown Voltage	V_{CEO}	-140	
Emitter-Base Breakdown Voltage	V_{EBO}	-6	
Collector Current (Continuous)	I_C	-4	A
Collector Current (Peak)	I_{CM}	-10	A
Base Current	I_B	-3	A
Power Dissipation	P_D	1	W
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	68	$^{\circ}\text{C}/\text{W}$
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	3	$^{\circ}\text{C}/\text{W}$
Junction Temperature Range	T_J	-55~+150	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55~+150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS (T_A=25°C)


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	V _{(BR)CBO}	I _C =-100μA, I _E =0	-180			
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	I _C =-10mA, I _B =0	-140			V
Emitter-Base Breakdown Voltage	V _{(BR)EBO}	I _E =-100μA, I _C =0	-6			
Collector Cut-off Current	I _{CBO}	V _{CB} = -150V, I _E =0			-50	nA
		V _{CB} = -150V, I _E =0, T _A = 100°C			-1	μA
Emitter Cut-off Current	I _{EBO}	V _{EB} = -6V, I _C =0			-10	nA
DC Current Gain	h _{FE}	V _{CE} = -5V, I _C = -10mA	100			
		V _{CE} = -5V, I _C = -1A	110		300	
		V _{CE} = -5V, I _C = -3A	75			
		V _{CE} = -5V, I _C = -10A		10		
Collector-Emitter Saturation Voltage	V _{CE(sat)}	I _C = -100mA, I _B = -5mA			-0.06	V
		I _C = -500mA, I _B = -50mA			-0.12	
		I _C = -1A, I _B = -100mA			-0.15	
		I _C = -3A, I _B = -300mA			-0.37	
Base-Emitter Saturation Voltage	V _{BE(sat)}	I _C = -3A, I _B = -300mA			-1.11	V
Base-Emitter Voltage	V _{BE(on)}	I _C = -3A, V _{CE} = -5V			-0.95	V
Transition Frequency	f _T	V _{CE} = -10V, I _C = -100mA, f = 50MHz		110		MHz
Output Capacitance	C _{ob}	V _{CB} = -20V, f = 1MHz		40		pF
Turn-on Time	t _{on}	I _C = -1A, I _{B1} = -100mA I _{B2} = 100mA, V _{CC} = -50V		68		ns
Turn-off Time	t _{off}			1030		

TYPICAL CHARACTERISTICS


h_{FE} vs. I_C




$V_{CE(sat)}$ vs. I_C



$V_{BE(sat)}$ vs. I_C




$V_{BE(ON)}$ vs. I_C




SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak)		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_r) (Liquidus)	217°C
	Time (min to max) (t_r)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C



SOT-223 PACKAGE DIMENSIONS



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.40		1.70	0.055		0.067
A1	0.01		0.06	0.001		0.002
B	2.90		3.10	0.114		0.122
B1	0.60		0.80	0.024		0.031
C	0.22		0.32	0.009		0.013
D	6.30		6.70	0.248		0.264
E	3.30		3.70	0.130		0.146
F		4.60			0.181	
F1		2.30			0.091	
G	0.70		1.10	0.028		0.043
H	1.50		2.00	0.059		0.079
J	6.70		7.30	0.264		0.287
K		0.90			0.035	

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
FZT955	SOT-223	2500PCS	13"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware' s global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.