

FEATURES

- Package optimized for high-speed lines
- Protects two 5V and two 28V data lines
- Low leakage current
- Low clamping voltage

APPLICATIONS

- USB Type-C
- High-speed data lines
- PD Charger or Adapter



DFN2510-10L


5B28O
Marking

IEC COMPATIBILITY

- IEC61000-4-2 (ESD) $\pm 30\text{kV}$ (air), $\pm 30\text{kV}$ (contact)
- IEC61000-4-4 (EFT) 40A (5/50ns)

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003



Schematic Symbol

THERMAL CONSIDERATIONS



Symbol	Parameter	Value	Unit
P_{PP}	Peak Pulse Power ($t_p=8/20\mu\text{s}$ waveform) Pin1 or Pin5 to Pin3&8	138	Watts
P_{PP}	Peak Pulse Power ($t_p=8/20\mu\text{s}$ waveform) Pin2 or Pin4 to Pin3&8	90	Watts
V_{ESD}	ESD per IEC 61000-4-2 (Air) Pin1 or Pin5 to Pin3&8	20	kV
V_{ESD}	ESD per IEC 61000-4-2 (Contact) Pin1 or Pin5 to Pin3&8	13	kV
V_{ESD}	ESD per IEC 61000-4-2 (Air) Pin2 or Pin4 to Pin3&8	30	kV
V_{ESD}	ESD per IEC 61000-4-2 (Contact) Pin2 or Pin4 to Pin3&8	30	kV
T_J	Operating Temperature Range	-55 to +125	°C
T_{STG}	Storage Temperature Range	-55 to +150	°C

ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
V_{RWM}	Reverse Stand-off Voltage	Pin1 or Pin5 to Pin3&8			28	V
V_{RWM}	Reverse Stand-off Voltage	Pin2 or Pin4 to Pin3&8			5	V
V_{BR}	Reverse Breakdown Voltage	$I_T=1mA$ Pin1 or Pin5 to Pin3&8	30			V
V_{BR}	Reverse Breakdown Voltage	$I_T=1mA$ Pin2 or Pin4 to Pin3&8	5.6			V
I_R	Reverse Leakage Current	$V_{RWM}=28V$ Pin1 or Pin5 to Pin3&8			100	nA
I_R	Reverse Leakage Current	$V_{RWM}=5V$ Pin2 or Pin4 to Pin3&8			100	nA
V_C	Clamping Voltage	$I_{PP}=2.5A, t_p=8/20\mu s$ Pin1 or Pin5 to Pin3&8			55	V
V_C	Clamping Voltage	$I_{PP}=6A, t_p=8/20\mu s$ Pin2 or Pin4 to Pin3&8			15	V
C_J	Off State Junction Capacitance	$V_R=0V, f=1MHz$ Pin1 or Pin5 to Pin3&8			18	pF
C_J	Off State Junction Capacitance	$V_R=0V, f=1MHz$ Pin2 or Pin4 to Pin3&8			15	pF


Note: I/O pins are pin 1/2/4/5; GND pins are pin 3/8; pin 6/7/9/10 are NC and can be connected with any pin.

CHARACTERISTIC CURVES




SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C




DFN2510-10L PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.40	0.65	0.016	0.026
A1	0	0.05	0	0.002
A2	(0.13)		(0.005)	
b	0.15	0.25	0.006	0.010
b1	0.35	0.45	0.014	0.018
D	2.40	2.60	0.094	0.102
E	0.90	1.10	0.035	0.043
e	0.50BSC		0.020BSC	
L	0.30	0.45	0.012	0.018
N	8		8	
aaa	0.08		0.003	
bbb	0.10		0.004	

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters	Inches
C	0.87	0.034
G	0.20	0.008
P	0.50	0.020
P1	1.00	0.039
X	0.20	0.008
X1	0.40	0.016
Y	0.68	0.027
Y1	1.55	0.061
Z	1.55	0.061

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
SE21T09U285D	DFN2510-10L	3000PCS	7"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.