

FEATURES



- | Surface-mounted package
- | Super Trench
- | Low Thermal Resistance
- | Low ciss

APPLICATION

- | Motor drivers
- | DC - DC Converter

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003



ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Drain-Source Voltage $T_c=25^\circ\text{C}$	V_{DS}	40	V
Drain Current (Pulsed) $T_c=25^\circ\text{C}, V_{GS}=10\text{V}$	I_{DM}^{***}	47	A
Drain Current $T_c=25^\circ\text{C}, V_{GS}=10\text{V}$	I_D^*	25	A
Gate-Source Voltage $T_c=25^\circ\text{C}$	V_{GS}	± 20	V
Total Power Dissipation $T_c=25^\circ\text{C}$	P_{tot}^*	35	W
Diode Forward Current $T_c=25^\circ\text{C}$	I_S	25	A
Single Pulsed Avalanche Energy $V_{DD}=40\text{V}, L=1.0\text{mH}$	E_{AS}^*	80	mJ
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55 to 150	$^\circ\text{C}$
Thermal Resistance – Junction to Ambient	$R_{\theta JA}^*$	62.5	$^\circ\text{C/W}$
Thermal Resistance- Junction to Case	$R_{\theta JC}^*$	3.5	$^\circ\text{C/W}$

Notes:

* Surface Mounted on 1 in² pad area, $t \leq 10$ sec

** Pulse width ≤ 300 us, duty cycle $\leq 2\%$

*** Limited by bonding wire

ELECTRICAL CHARACTERISTICS (T_A=25°C)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_{DS}=250\mu A$	40			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_{DS}=250\mu A$	1.0		2.0	V
Drain Leakage Current	I_{DSS}	$V_{DS}=36V, V_{GS}=0V$			1	μA
		$V_{DS}=36V, V_{GS}=0V, T_J=85^{\circ}C$			30	μA
Gate Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
On-State Resistance	$R_{DS(on)}^a$	$V_{GS}=10V, I_D=4A$		14	15	m Ω
		$V_{GS}=4.5V, I_D=3A$		22	24	m Ω
Diode Characteristics						
Diode Forward Voltage	V_{SD}^a	$I_{SD}=4A, V_{GS}=0V$			1.3	V
Reverse Recovery Time	t_{rr}	$I_{SD}=4A$ $dI_{SD}/dt=100A/\mu s$		13		nS
Reverse Recovery Charge	Q_{rr}			5.8		nC
Dynamic Characteristics ^b						
Input capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=22.5V,$ Frequency = 1 MHz		308		pF
Output capacitance	C_{oss}			124		pF
Reverse transfer capacitance	C_{rss}			34		pF
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=22.5V, V_{GEN}=10V$ $R_G=4.5\Omega, R_L=1.12\Omega,$ $I_D=4A$		5.1		nS
Turn-on Rise Time	t_r			41		nS
Turn-Off Delay Time	$t_{d(off)}$			14		nS
Turn-Off Fall Time	t_f			7.4		nS
Gate Charge Characteristics ^b						
Total Gate Charge	Q_g	$V_{DS}=10V, V_{GS}=22.5V, I_{DS}=4A$		8		nC
Gate-Source Charge	Q_{gs}			2.1		nC
Gate-Drain Charge	Q_{gd}			1.9		nC

Notes:

a : Pulse test ; pulse width ≤ 300μs, duty cycle ≤ 2 %

b : Guaranteed by design, not subject to production testing

PARAMETER CHARACTERISTIC CURVE

Figure1: Power Capability




Figure2: Current Capability




Figure3: Safe Operation Area




Figure 4: Transient Thermal Impedance













Figure 5: Output Characteristics

Figure 6: On Resistance

Figure 7: Transfer Characteristics

Figure 8: Normalized Threshold Voltage


Figure 9: Normalized On Resistance

Figure 10: Body Diode Characteristics

Figure 11: Capacitance

Figure 12: Gate Charge


PDFN3.3x3.3-8L PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	3.05	3.25	0.120	0.128
B	3.15	3.55	0.124	0.140
C	0.65		0.026	
D	0.32		0.013	
E	0.835	1.235	0.033	0.049
F	0.835	1.235	0.033	0.049
G	1.53	1.93	0.060	0.076
H	0.49	0.89	0.020	0.035
I	3.10	3.50	0.122	0.138
J	0.65	0.90	0.026	0.035
K	0.152		0.006	

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
SNNM1504QD	PDFN3.3×3.3-8L	5000PCS	13"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.