




FEATURES

- | High Density Cell Design For Low $R_{DS(On)}$
- | Voltage Controlled Small Signal Switch
- | Rugged and Reliable
- | High Saturation Current Capability
- | ESD Protected


SOT-23

Marking

Schematic Symbol

APPLICATION

- | Direct logic-level interface: TTL/CMOS
- | Drivers: relays, solenoids, lamps
- | hammers, display, memories, etc.
- | Battery operated systems
- | Solid-state relays

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

ABSOLUTE MAXIMUM RATINGS

Parameter	Conditions	Symbol	Value	Unit
Drain-Source Voltage	$T_A=25^\circ\text{C}$	V_{DS}	-20	V
Drain Current- Pulsed	$T_A=25^\circ\text{C}$	V_{GS}	± 8	V
Drain Current	$T_A=25^\circ\text{C}, V_{GS}=-4.5\text{V}$	I_D^*	-4	A
Pulsed Drain Current	$T_A=25^\circ\text{C}, V_{GS}=-4.5\text{V}$	I_{DM}^{**}	-16	A
Total Power Dissipation	$T_A=25^\circ\text{C}$	P_{tot}	0.83	W
	$T_A=100^\circ\text{C}$		0.3	W
Junction Temperature		T_J	150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55 to 150	$^\circ\text{C}$
Maximum Resistance – Junction to Ambient	$T_A=25^\circ\text{C}$	I_S	-1	A
Thermal Resistance- Junction to Ambient		$R_{\theta JA}^*$	150	$^\circ\text{C/W}$

Notes:

* Surface Mounted on 1 in² pad area, $t \leq 10$ sec

** Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$

ELECTRICAL CHARACTERISTICS (T_A=25°C)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _{DS} =-250μA	-20			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _{DS} =-250μA	-0.5		-1	V
Drain Leakage Current	I _{DSS}	V _{DS} =-16V, V _{GS} =0V			-1	μA
Drain Leakage Current (T _J =85°C)					-30	μA
Gate Leakage Current	I _{GSS}	V _{GS} =±8V, V _{DS} =0V			±10	μA
On-State Resistance	R _{DS(on)} ^a	V _{GS} =-4.5V, I _{DS} =-4A		30	37	mΩ
		V _{GS} =-2.5V, I _{DS} =-3A		42	52	mΩ
		V _{GS} =-1.8V, I _{DS} =-2A		57	72	mΩ
Diode Characteristics						
Diode Forward Voltage	V _{SD} ^a	I _{SD} =0.2A, V _{GS} =0V	-0.5		-1.3	V
Reverse Recovery Time	t _{rr}	I _{SD} = -4A, dI _{SD} /dt=100 A/μs		49.5		ns
Reverse Recovery Charge	Q _{rr}			16.5		nC
Dynamic Characteristics^b						
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =-10V, Frequency = 1 MHz		1121		pF
Output capacitance	C _{oss}			161		pF
Reverse transfer capacitance	C _{rss}			148		pF
Turn-on Delay Time	t _{d(on)}	V _{DS} = -10V, V _{GEN} = -4.5V R _G = 3.3Ω, R _L = 2.5Ω, I _{DS} = -4A		5.5		ns
Turn-on Rise Time	t _r			60.5		ns
Turn-Off Delay Time	t _{d(off)}			89		ns
Turn-Off Fall Time	t _f			73		ns
Gate Charge Characteristics^b						
Total Gate Charge	Q _g	V _{GS} =-4.5V, V _{DS} =-10V, I _{DS} =-4A		17.4		nC
Gate-Source Charge	Q _{gs}			1.9		nC
Gate-Drain Charge	Q _{gd}			4.1		nC

Notes:

a : Pulse test ; pulse width ≤ 300μs, duty cycle ≤ 2 %

b : Guaranteed by design, not subject to production testing

PARAMETER CHARACTERISTIC CURVE

Figure1: Power Dissipation




Figure2: Current Capability




Figure3: Safe Operation Area




Figure 4: Transient Thermal Impedance




Figure 5: Output Characteristics




Figure 6: Drain-Source On Resistance




Figure 7: Transfer Characteristics




Figure 8: Normalized Threshold Voltage




Figure 9: Normalized On Resistance




Figure 10: Current Diode Forward




Figure 11: Capacitance






Figure 12: Gate Charge




SOT-23 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.80	3.05	0.110	0.120
B	1.20	1.40	0.047	0.055
C	0.90	1.15	0.035	0.045
D	0.37	0.50	0.015	0.020
G	1.75	2.05	0.069	0.081
H	0.01	0.100	0.001	0.004
J	0.085	0.180	0.003	0.007
K	0.35	0.69	0.014	0.029
L	0.89	1.02	0.035	0.040
S	2.10	2.65	0.083	0.104
V	0.45	0.60	0.018	0.024

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.71	0.97	0.028	0.038
B	1.88	2.13	0.074	0.084
C	0.71	0.97	0.028	0.038
D	0.81	1.07	0.032	0.042

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
SPM3415E	SOT-23	3000PCS	7"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.