


FEATURES

- | Metal silicon junction, majority carrier conduction
- | For surface mounted applications
- | Low power loss, high efficiency
- | High forward surge current capability
- | For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications



SMAF



Schematic Symbol

MECHANICAL DATA

- | Case: SMAF
- | Mounting Position: Any

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter		Symbol	SS 12AF	SS 14AF	SS 16AF	SS 18AF	SS 110AF	SS 112AF	SS 115AF	SS 120AF	Unit
Marking			SS12	SS14	SS16	SS18	SS110	SS112	SS115	SS120	
Repetitive Peak Reverse Voltage		V _{RRM}	20	40	60	80	100	120	150	200	V
Reverse Voltage,total RMS Value		V _{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage		V _{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current		I _{F(AV)}	1.0								A
Surge Peak Forward Surge Current, 8.3ms Single Half Sine-Wave Superimposed On Rated Load Per Diode		I _{FSM}	25								A
Max Instantaneous Forward Voltage at 1 A		V _F	0.55		0.70		0.85		0.90		V
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _A =25°C	I _R	0.3				0.2		0.1		mA
	T _A =100°C		10				5		2		mA
Typical Junction Capacitance ¹⁾		C _j	110		80						pF
Typical Thermal Resistance Note ²⁾		R _{θJA}	95								°C/W
Operating Junction and Storage Temperature Range		T _J , T _{STG}	-55 to +150								°C

Note1): Measured at 1 MHz and applied reverse voltage of 4 V D.C

Note2): P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas

CHARACTERISTIC CURVES

Fig. 1- Forward Current Derating Curve




Fig. 2-Typical Reverse Characteristics




Fig. 3-Typical Forward Characteristic




Fig. 4-Typical Junction Capacitance







Fig. 5-Maximum Non-Repetitive Peak Forward Surge Current

Fig. 6-Typical Transient Thermal Impedance


SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak $T_{s(max)}$) to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C




SMAF PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min	Max	Min	Max
A	1.35	1.60	0.053	0.063
B	3.40	3.80	0.134	0.145
C	2.40	2.80	0.094	0.110
D	0.95	1.45	0.037	0.057
F	0.15	0.22	0.006	0.009
G	4.40	4.80	0.173	0.189

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min	Max	Min	Max
A	1.70	-	0.067	-
B	2.50	-	0.098	-
C	-	1.5	-	0.059
D	2.50	-	0.098	-
E	6.50REF		0.256REF	

ORDERING INFORMATION

Part Number	Package	QTY/Reel	Reel Size
SS12AF-120AF	SMAF	5000PCS	13"

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware' s global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.